

# ThinkSystem SR590

## Balanced performance and scalability



### Powerful and Balanced

Designed for rack environments that require peak two-socket performance and sizeable memory capacity, the Lenovo ThinkSystem SR590 can tackle cloud and Big Data environments for medium and large enterprises. The SR590 is a balanced, midrange rack server that also works well for small-scale virtualization, collaboration and productivity applications, as well as caching and logging.

Two second-generation Intel® Xeon® Scalable Family processors increase agility and manage data-rich, high-demand workloads with up to a 1.5x memory bandwidth increase over the previous generation. Intel® Optane™ DC Persistent Memory combined with up to 1TB of 2933MHz TruDDR4 memory capacity enable applications to run faster and more efficiently and boost business performance at a lower cost and higher overall value.†

### Flexible and Expandable

The SR590 supports up to 16 hot-swap 2.5" or 14 hot-swap or simple-swap 3.5" drive bays. Up to four of the 2.5" or 3.5" bays can be AnyBay, capable of supporting not only SAS/ SATA drives, but also direct-connect NVMe drives (which bypass the SAS bus) for the ultimate in storage performance. In addition, the SR590 supports SAS and SATA HDDs and SSDs with up to 12Gb SAS throughput, as well as up to two M.2 drives for faster, more secure OS boot.

The SR590 provides storage flexibility, NIC expansion in multiple form factors, including LOM, ML2, and PCIe, and replaceable I/O riser cards for varied adapter slot configurations.

### Reliable and Secure

Lenovo servers have been the most reliable in the industry for several years. They were ranked #1 yet again in the latest ITIC survey of x86 server reliability.\* The SR590 is no exception, including many features that contribute to the reliability and security of the server and your all-important data.

ThinkShield is a comprehensive end-to-end approach to security that begins with development and continues through supply chain and the full life cycle of the device. From the data center to the edge of the network our priority is protecting your business with each product.

Lenovo XClarity Controller is the embedded management engine in all ThinkSystem servers that is designed to standardize, simplify, and automate foundation server management tasks. Lenovo XClarity Administrator is a virtualized application that centrally manages ThinkSystem servers, storage, and networking, which can reduce provisioning time up to 95% versus manual operation. Running XClarity Integrator helps you streamline IT management, speed provisioning, and contain costs by seamlessly integrating XClarity into an existing IT environment.

Lenovo™

These features result in an ideal server for proxy caching, cloud, CRM, security, virtualization, media streaming, Big Data, databases, database-driven Web serving, mail serving, and many other workloads.


## Specifications

<b>Form Factor</b>	2U
<b>Processors</b>	Up to 2 second-generation Intel® Xeon® Platinum 150W, up to 26 cores per CPU
<b>Memory</b>	Up to 1TB of 2933MHz TruDDR4 memory in 16 slots
<b>Expansion Slots</b>	Up to 6x PCIe 3.0 on replaceable riser cards for multiple I/O configurations
<b>Drive Bays</b>	Up to 16x 2.5" or 14x 3.5" hot-swap or up to 8x 3.5" simple-swap; optional 4x AnyBay bays
<b>Internal Storage</b>	Up to: 168TB (3.5" SAS/SATA HDD); 107.6TB (3.5" SSD); 38.4TB (2.5" SAS/SATA); 122.9TB (2.5" SSD); 16TB (direct-connect 2.5" NVMe); up to 2x M.2 boot drives
<b>Network Interface</b>	2 GbE ports standard; LOM interface standard; optional ML2
<b>NIC ports</b>	2x GbE standard; 1x GbE dedicated management standard; optional up to 2x 1GbE, 2x 10GBase-T, or 2x 10GBase SFP+
<b>Power Supply</b>	Up to 2x hot-swap/redundant 550W/750W Platinum, 750W Titanium
<b>High-Availability</b>	Hot-swap HDDs/SSDs/NVMe, hot-swap PSUs and fans, light path diagnostics, PFA for all major components, ASHRAE A4 support (with limits), optional XClarity Pro with Call Home feature.
<b>Security Features</b>	ThinkShield, locking bezel; locking top cover; TPM 2.1 standard; optional TCM
<b>RAID Support</b>	HW RAID 0, 1, 10, 5, 50 standard on hot-swap models for 2.5"; SW RAID 0, 1, 10, 5 on simple-swap 3.5" models
<b>Management</b>	XClarity Administrator; XClarity Controller (embedded hardware); optional XClarity Pro
<b>OS Support</b>	Microsoft, SUSE, Red Hat, VMware. Visit <a href="http://lenovopress.com/osig">lenovopress.com/osig</a> for details.
<b>Limited Warranty</b>	1-year and 3-year customer replaceable unit and onsite service, next business day 9x5

## For More Information

To learn more about the Lenovo ThinkSystem SR590, contact your Lenovo representative or Business Partner or visit [www.lenovo.com/thinksystem](http://www.lenovo.com/thinksystem). For detailed specifications, consult the [SR590 Product Guide](#).

‡ Based on Intel internal testing, August 2018. \* [ITIC 2018 Global Reliability Report](#).



© 2019 Lenovo. All rights reserved.

**Availability:** Offers, prices, specifications and availability may change without notice. Lenovo is not responsible for photographic or typographic errors. **Warranty:** For a copy of applicable warranties, write to: Lenovo Warranty Information, 1009 Think Place, Morrisville, NC, 27560. Lenovo makes no representation or warranty regarding third-party products or services. **Trademarks:** Lenovo, the Lenovo logo, AnyBay, Lenovo XClarity, ThinkSystem, and TruDDR4 are trademarks or registered trademarks of Lenovo. Intel®, Optane™, and Xeon® are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. Microsoft® is a trademark of Microsoft Corporation in the United States, other countries, or both. Other company, product, or service names may be trademarks or service marks of others. Document number DS0016, published November 28, 2017. For the latest version, go to [lenovopress.com/ds0016](http://lenovopress.com/ds0016).

